to ensure that existing systems, such as the Inmarsat and the AMSC systems, would not be subject to additional coordination procedures. At WRC-95, the U.S. should clarify this position with appropriate language in the allocations.

### 3.6.6. **Summary**

This section has identified areas where Regulatory/Procedural proposals need to be developed for WRC-95. In the Appendix are excerpts from ITU-R documents which provide more detailed descriptions of the methods and calculations referenced in the text.<sup>2</sup>

### 3.7 Proposals

### 3.7.1 Sharing Proposals

**MOD 731E** 

The use of the band 1610-1626.5 MHz by the mobile-satellite service (Earth-to-space) and by the radiodetermination-satellite service (Earth-to-space) is subject to the application of the coordination and notification procedures set forth in Resolution 46 (WARC-92). A mobile earth station operating in either of the services in this band shall not produce an a mean e.i.r.p. density in excess of -15 dB (W/4 kHz) in the part of the band used by systems operating in accordance with the provisions of No. 732, unless otherwise agreed by the affected administrations. In the part of the band where such

will not accept any commitment for this form of coordination arising from omission of the term "non-geostationary" in the text of certain footnotes, e.g. Footnote Nos. 726x and 7xx, to the Table of Frequency Allocations in Article 8. This reservation is made on behalf of all national and international organizations for whose frequency assignments the two countries are the notifying Administrations.

See Final Protocol No. 679 WARC-92 Final Acts. The text reads:

Referring to statements relating to the frequency range below 3 GHz concerning mobile-satellite services, it is necessary to highlight an oversight in drafting and reading texts which could lead to a new and unnecessary burden of coordination between geostationary space stations and terrestrial services in certain frequency bands. Accordingly, the above Administrations will not accept any commitment for this form of coordination arising from omission of the term "non-geostationary" in the text of certain footnotes, e.g. Footnote Nos. 726x and 7xx, to the Table of Frequency Allocations in Article 8. This reservation is made on behalf of all national and international organizations for whose frequency assignments the two countries are the notifying Administrations.

systems are not operating, a value of -3 dB (W/4 kHz) is applicable. Stations of the mobile satellite service shall not cause harmful interference to, or claim protection from, stations in the aeronautical radionavigation service, stations operating in accordance with the provisions of No. 732 and stations in the fixed service operating in accordance with the provisions on No. 730.

Reason

Inclusion of the term "mean" is intended to clarify how the e.i.r.p. density limit should be measured. The text proposed for deletion at the end of this provision is unnecessary to protect the primary allocation status of the identified services and creates confusion and ambiguity concerning the primary status of the mobile-satellite service in the 1610-1626.5 MHz band.

**SUP 733E** 

Harmful interference shall not be caused to stations of the radio astronomy service using the band 1610.6-1613.8 MHz by stations of the radiodetermination satellite and mobile satellite services. (No. 2904 applies.)

Reason

This provision is unnecessary to protect the primary allocation status of radio astronomy and creates confusion and ambiguity concerning the status of the satellite services that are allocated on a primary status in the 1610-1626.5 MHz band.

**MOD 746B** 

In the band 2160-2200 MHz coordination of space stations of the mobile-satellite service with respect to terrestrial services is required only if the power flux density or <u>Fractional Degradation Percentage</u> at the Earth's Surface exceeds the <u>threshold limits in No. 2566</u>, in <u>Recommendation (TG 2-2/TEMP/89 (Rev2)</u>.

**NOC 746C** 

In the United States, the use of the bands 1970-2010 MHz and 2160-2200 MHz by the mobile-satellite service shall not commence before 1 January 1996

Reason

This facilitates the early introduction of emerging mobilesatellite technology.

**MOD 753F** 

The use of the band 2483.5-2500 MHz by the mobile-satellite service and the radiodetermination-satellite service is subject to the application of the coordination and notification procedures set forth in Resolution 46 (WARC-92). Coordination of space stations of the mobile-satellite and radiodetermination-satellite services with respect to terrestrial services is required only if the power-flux density

produced at the Earth's surface exceeds: the limits in No. 2566.

-150 dB (W/m<sup>2</sup>) in any 4 kHz band for angles of arrival between 0 and 5 degrees above the horizontal plane;

-150 + 0.65 ( $\delta$ -5) dB (W/m<sup>2</sup>) in any 4 Khz band for angles of arrival  $\delta$  (in degrees) between 5 and 25 degrees above the horizontal plane;

-137 dB (W/m<sup>2</sup>) in any 4 kHz band for angles of arrival between 25 and 90 degrees above the horizontal plane.

These limits relate to the power flux-density which would be obtained under assumed free-space conditions.

In respect of assignments operating in this band, the provisions of Section II, paragraph 2.2 of Resolution 46 (WARC-92) shall also be applied to geostationary transmitting space stations with respect to terrestrial stations.

Reason

To facilitate the introduction of mobile-satellite systems in this band while providing adequate protection of analog point-to-point and multipoint fixed systems in the band.

# 3.7.2 New Allocations

MHz 1525 - 1530

	Allocation to Services	
Region 1	Region 2	Region 3
1525 - 1530	1525 - 1530	1525 - 1530
SPACE OPERATION (space-to-Earth)	SPACE OPERATION (space-to-Earth)	SPACE OPERATION (space-to-Earth)
FIXED	MOBILE-SATELLITE (space-to-Earth)	FIXED
MOBILE-SATELLITE (space-to-Earth)	Earth Exploration-Satellite	MOBILE-SATELLITE (space-to-Earth)
MARITIME  MOBILE SATELLITE  (space to Earth)		
Land Mobile-Satellite (space to Earth) 726B	Fixed	Earth Exploration-Satellite
Earth Exploration-Satellite	Mobile 723	Mobile 723 724
Mobile except aeronautical mobile 724		
722 723B 725 726A 726D	722 723A 726A 726D	722 726A 726D

Reason: To make allocation generic.

MHz 1530 - 1533

	Allocation to Services	
Region 1	Region 2	Region 3
1530 - 1533	1530 - 1533	
SPACE OPERATION (space-to-Earth) MOBILE-SATELLITE	SPACE OPERATION (space-to-Earth)	
(space-to-Earth)	MARITIME MOBILE SATELL (space to Earth)	<del>ITE</del>
MARITIME  -MOBILE SATELLITE  (space-to-Earth)  LAND MOBILE	MOBILE-SATELLITE (space-to-Earth)	
-SATELLITE -(space to Earth)	LAND MOBILE SATELLITE (space to Earth)	
Earth Exploration-Satellite Fixed	Earth Exploration-Satellite	
Mobile except aeronautical	Fixed	
	Mobile 723	
722 723B 726A <u>726C</u> 726D	722 726A` 726C 726D	

### **MOD 726C**

The band 1530 -1544 MHz is allocated to the mobile-satellite (space-to-Earth) service, and the band 1626.5 - 1645.5 MHz is allocated to the mobile-satellite (Earth-to-space) service, on a primary basis subject to the following conditions: maritime mobile-satellite distress and safety communications shall have priority access and immediate availability over all other mobile-satellite communications operating under this provision. Communications of mobile-satellite system stations not participating in the global maritime distress and safety system (GMDSS) shall operate on a secondary basis to distress and safety communications of stations operating in the GMDSS. Account shall be taken of the priority of safety-related communications in the other mobile-satellite services.

Reason:

To make allocation generic.

# MHz 1533 - 1559

	Allocation to Services	
Region 1	Region 2 Region 3	
1533 - 1535	1533 - 1535	
SPACE OPERATION (space-to-Earth)	SPACE OPERATION (space-to-Earth)	
MARITIME  - MOBILE SATELLITE  - (space to Earth)	MARITIME MOBILE SATELLITE (space to Earth)	
MOBILE-SATELLITE (space-to-Earth)	MOBILE-SATELLITE (space-to-Earth)	
Earth Exploration-Satellite	Earth Exploration-Satellite	
Fixed	Fixed  Mobile 723	
Mobile except aeronautical mobile	Land Mobile Satellite	
Land Mobile  Satellite (space to Earth) 726B	-(space to Earth) 726B	
722 723B 726A <u>726C</u> 726D	722 726A 726C 726D	
1535 - 1544 MARITIME MOBILE SATELLITE  - (space-to-Earth)  Land Mobile-Satellite  - (space-to-Earth) 726B  MOBILE-SATELLITE (space-to-Earth)		
722 726A 726C 726	D 727	
1544 - 1545 MOBILE-SATEL (space-to-Earth)	LITE .	
722 726D 727 727A		

				A	locatio	n to Ser	vices	
		Region I				Region :	2	Region 3
1545	MOB	ce-to-Ea ILE-SAT to-Eart	ELLITE				·	<del>R)</del>
1555	- 1559 <del>- (sp</del> a	LA ce to Ea	ND MOBII	E SA	FELLI	FE.		
		ILE-SA] æ-to-Ear	TELLITE (th)					
	722	726A	726D	727	730	730A	730B	730C

Reason: To make allocations generic and to provide priority access and immediate availability for aeronautical and maritime distress and safety communications.

### **MOD 730C**

The band 1545 - 1559 MHz is allocated to the mobile-satellite (space-to-Earth) service, the band 1646.5 - 1660 MHz is allocated to the mobile-satellite (Earth-to-space) service, and the band 1660 - 1660.5 MHz is allocated to the mobile-satellite (Earth-to-space) and radio astronomy services, on a primary basis subject to the following conditions: the aeronautical mobile-satellite (R) service shall have priority access and immediate availability over all other mobile-satellite communications within a network operating under this provision; mobile-satellite systems shall be interoperable with the aeronautical mobile-satellite (R) service; account shall be taken of the priority of safety-related communications in the other mobile-satellite services.

# MHz 1626.5 - 1660.5

	Allocation to Services			
Region 1	Region 2 Region 3			
1626.5 - 1631.6	1626.5 - 1631.5			
MARITIME MOBILE - SATELLITE - (Earth-to-space)	MOBILE-SATELLITE (Earth-to-space)			
MOBILE-SATELLITE (Earth-to-space)				
Land Mobile Satellite (Earth to space) 726B	•			
722 726A <u>726C</u> 726D 727 730	722 726A 726C 726D 727 730			
(space to Earth) LAND MOBILE SATELLITE (Earth to space) (space to Earth) 726B  MOBILE-SATELLITE (Earth-to-space)				
	D 727 730 734A			
1645.5 - 1646.5 MOBILE-SATEL	1645.5 - 1646.5 MOBILE-SATELLITE (Earth-to-space)			
1646.5 - 1656.5 MOBILE-SATEI	LLITE (Earth-to-space)			
AERONAUTICAL MOBILE SATELLITE (R) - (Earth-to-space)				
722 726A 726D 7	27 729A 730 <u>730C</u> 734A			
1656.5 - 1660 MOBILE SATE	LLITE (Earth-to-space)			
LAND MOBILE SATELLITE (Earth to space)				
722 726A 726D 727	730 730A 730B 730C 734A			

				Alleca	tion to	Service	•
	Region	l			Regio	n 2	Region 3
1660 - 1660	.5 RA	DIO A	STRON	OMY			
F	AND M	OBILE :	SATELI	LITE (I	Sarth to	s <del>pace)</del>	
<u>M</u>	OBILE-	SATEL	LITE (F	arth-to-	space)		
722	726A	726D	730A	730B	730C	736	

### Reason:

To make allocations generic and to provide priority access and immediate availability for aeronautical and maritime distress and safety communications.

## MHz 1675 - 1710

	Allocation to Services	
Region 1	Region 2	Region 3
1675 - 1690  METEOROLOGICAL AIDS FIXED  METEOROLOGICAL-SATELLITE (space-to-Earth)  MOBILE except aeronautical mobile  MOBILE SATE (Earth-to-space)  722		JITE nobile
1690 - 1700 METEOROLOGICAL AIDS METEOROLOGICAL SATELLITE (space-to-Earth) MOBILE SATELLITE (Earth-to-space) Fixed Mobile except aeronautical mobile  671 722 741	1690 - 1700 METEOROLOG METEOROLOG (space-to-Earth  MOBILE SATE (Earth-to-spa	ICAL-SATELLITE ) LLITE ce)

MHz 1700 - 1710

	Allocation to Services
Region 1	Region 2 Region 3
1700 - 1710 FIXED METEOROLOGICAL- SATELLITE (space-to-Earth) MOBILE SATELLITE (Earth-to-space)	1700 - 1710 FIXED METEOROLOGICAL-SATELLITE (space-to-Earth)  MOBILE except aeronatical mobile MOBILE SATELLITE (Earth-to-space)
Mobile except aeronatical mobile 671 722 743A	671 722 743 <u>(Earth-to-space)</u>

MHz 2010 - 2200

	Allocation to Services
Re	gion 1 Region 2 Region 3
2010 - 2025	FIXED
MOBIL	E
MOBIL	E-SATELLITE (Earth-to-space)
746A	

2160 - <u>2165</u>	2160 - 2170	2160 - <u>2165</u>
FIXED MOBILE	FIXED MOBILE	FIXED MOBILE
746A	MOBILE-SATELLITE	746A
2165 - 2170	(space-Earth)	2165 - 2170
FIXED MOBILE	746A 726B 746C	FIXED MOBILE
MOBILE-SATELLITE (space-to-Earth)		MOBILE-SATELLITE (space-to-Earth)
746A		746A

# Reason:

To provide additional allocations for the mobile-satellite service.

### MHz 2300-2450

	Allocation to Services
Region 1  2300 - 2450  FIXED  Amateur  Mobile  Radiolocation	Region 2 Region 3  2300 - 2450 FIXED MOBILE except aeronautical mobile RADIOLOCATION Amateur
664 743A 752 <u>752A</u>	664 751 752 <u>752A</u>

- The band 2400 2500 MHz (centre frequency 2450 MHz) is designated for industrial, scientific and medical (ISM) applications. Radio services operating within this band must accept harmful interference which may be caused by these applications. ISM equipment operating in this band is subject to the provisions of No. 1815.
- ADD 752A The band 2300-2310 MHz may also be used by the Mobile-Satellite Service on a primary basis in either the space-to-Earth or Earth direction. The band 2390-2400 MHz may also be used by the Mobile-Satellite service (Earth-to-space) on a primary basis. The band 2402-2417 MHz may also be used by the Mobile-Satellite service (space-to-Earth) on a primary basis.

Reason to provide more spectrum for MSS on a global basis.

- 3.7.3 Regulatory Changes to Radio Regulations Revisions to Resolution 46
- Add 2.5 bis

  Those fixed service assignments, identified in 2.5.4 and 2.5.5 where the PFD/FDP in Recommendation (TG 2-2/TEMP.89 (Rev1) are exceeded, but receive protection in accordance with the application of the method in Recommendation (TG2-2/TEMP/100 (Rev2) are excluded from the requirement to coordinate.
- Add 2.7.1 bis

  i) shall assess the systems compliance with the thresholds set forth in Recommendation (TG 202/TEMP/89 (Rev2) of the systems resultant parameters do not exceed the thresholds in this Recommendation in the bands concerned. There is no need for coordination with the fixed services.
  - ii) If the system parameters exceed the thresholds in 2.7.1 bis (i) the Bureau shall use the standard computation program in Recommendation (TG 202/TEMP/100 (Rev2) taking into account the

system specific characteristics and the referenced characteristics of the FS systems, to calculate interference levels to identify geographic areas in which the protection criteria referenced in Rec. (TG 202/TEMP/100 (Rev1) for the referenced analogue/digital FS systems are not met.

iii) The BR shall publish both the Appendix 3 parameters and the list of administrations which it considers potentially affected.

### Add 2.8 bis

- i) If, within the six month period referred to above, no objection is received from any administration, including those identified by the Bureau in the Special Section, the notifying administration is considered as having successfully coordinated the non-GSO MSS system with the fixed services.
- ii) Upon receipt of the publication mentioned in Section 2.7.2, an administration which has not been included in the list of affected administrations by the BR may, within the six month period referred to above, request to be included if it considers that it could be affected (Paragraph 2.8 of Annex to Resolution 46). However, this inclusion needs to be validated by the BR on the basis of the criteria.
- iii) The notifying administration and any administration that provided an objection on the planned non-GSO MSS system within the six month period would enter into detailed coordination consultations using actual FS stations and characteristics.

Reason

To provide for use of the system specific characteristics of MSS systems in certain 1-3 GHz downlink MSS allocations.

### MOD Footnote (1) to Section 3.1, Res. 46

The coordination area is defined as the service area in which it is intended to operate the typical earth stations, extended in all directions by a coordination distance determined according to ITU-R IS 847 except for aircraft stations where a coordination distance of 500 Km and the method of ITU-R IS 850 should be used. or as a circular zone with a radius of 500 Km centered on the coordinates of the fixed earth station. For a service area in which aircraft earth stations operate, the coordination area is the service area extended in all directions by a coordination distance of 1000 Km.

Reason

To reduce the coordination area for Non-GSO MSS earth stations.

### Add Section II, 2.3.

For the assignments identified in Section 2.5 those which are in the affected region may be determined by the calculation method in Draft New Recommendation (WP-8D/TEMP/1 (Rev.1), December 8, 1994.

Reason

To define the region for coordination of MSS system assignments.

# APPENDIX 3.8.1 IWG-3 - MSS ABOVE 1 GHZ - LIST OF PARTICIPANTS

Audrey Allison

FCC

Melvin Barmat

Jansky\Barmat

Richard Barnet

TRW

Jeff Binckes

**COMSAT Mobile Communications** 

Sandra Bisbey

Telecommunications Systems

James R. Carroll

SFA

T. Stephen Cheston Christine M. DiLapi James G. Ennis Iridium, Inc. Motorola Iridium, Inc.

Richard Evans

AMSC

Ben C. Fisher

Fisher, Wayland

Diane Garfield Thomas Gergely State NSF

Richard Gould

Telecommunications Systems

William Hatch Cecily Holiday William Horne NTIA FCC STEL

Donald Jansky

Jansky/Barmat

Andy Haire

MCI

Steven Heppe Kris Hutchison Ken Keane Loral Qualcomm
Aeronautical Radio
Winston & Strawn

Thomas Keller Kristi Kendall Perry Klein Damon C. Ladson VLBMH FCC AMSAT FCC

CCI

Barry Lambergman

Mark N. Lewellen

Fletcher Heald

Ronald Lepkowski Lon Levin

AMSC
Westinghouse
U.S. Air Force

Robert May Edward Miller

U.S. Air Force

Edward Miller Sam Nguyen

COMSAT Mobile Communications

Kaye Nilson

Compass Rose International for U.S. Coast guard

Walter Pappas

BA

Mahasti Pourdastan Jay Ramasastry

LQP/Qualcomm

Brian Ramsey

NTIA

Edward Reinhart

Consultant for Hughes Aircraft

Glenn Richards

Fisher, Wayland

Warren G. Richards Paul Rinaldo Bev Sincavage Thomas Sullivan State ARRL LTA CSC

Leslie Taylor Wes Vivian Leslie Taylor Associates
Wireless Cable Association

James Vorhies NTIA

Alix Watson
Jack Wengryniuk
Gerry Wiggen
Richard Wilder
Bret Wilson

Air Touch Communications COMSAT LABS SFA ARRL Rockwell

2

0136

# Appendix 3.8.2 IWG-3 - MSS ABOVE 1 GHZ LIST OF DOCUMENTS

No.	Source	Title
01	Richards	Agenda - June 16, 1994
02	WRC-93	Res. 1 -Agenda for WRC-95
03	IAC	IWG-3 Terms of Reference
04	IAC	IWG-3 Proposed Work Program
05	IAC	Proposed IAC Meeting Schedule
06	Richards	Meeting for IWGs 3, 4 & 5
07	Jansky	1-3 GHz MSS Spectrum Requirements
08	WRC-93	Rec. 2, MSS Networks Published Under Res 46
09	ITU-RB	Report on the Experience of the RB in the
		Application of Res. 46
10/2	Levin	History of MSS International Allocations
11/2	LTaylor	Spectrum Requirements Section of IWG-3
	•	Preliminary Report
12	Levin	Proposal for the Bands 1530-1544/1626.5-
		1645.5 MHz and 1545-1559/1646.5-1660.5 MHz
13	Barmat	Proposal for FN 731E, 1610-1626.5 MHz
14	Sullivan	Proposal for the Band 1675-1710 MHz
15	Binckes	Proposal for FN 746B, 1970-2010/2160-2200 MHz
16	Levin	Proposal for the Bands 2010-2025/2165-2170 MHz
17/2	Lewellen	Proposal for Revision of Power Flux Density (PFD)
		Limits in the 2483.5-2500 MHz Band as Provided
		in Footnote 753F and RR 2566
18	Binckes	Proposal for Rec. 2, MSS Networks
		Published Under Res. 46
19	Jansky	Experience with Application of Resolution 46 and
		Associated RR Provisions (TG 8/3-12)
20	Carroll	Regulatory, Operational and Technical
		Constraints, 1492-1525 MHz Band
21	Lepkowski	Relative Status of Services in FN 731E
22	DiLapi	Modification of the Date of Entry into
		Force of 2 GHz MSS Allocations
23	Jansky	A Framework for pfd Triggers in the MSS
		Bands
24	Jansky	Implementation of NGSO MSS Coordination
		Method
25	Binckes	Applicability of RR 2566 to FN 746B
27	Levin	Mobile Satellite Service Allocations in the 2500-
		2535 MHz (space to Earth) and 2670-2690 MHz
		(Earth to space) Bands
28	Ladson	Minutes - June 16, 1994 Meeting
29	EC	Comments on FCC Notice of Proposed Rulemaking
30	ITU Council	Future Conferences of the Union
31	Fisher	Minutes - July 5, 1994 Meeting
32	Long	Summary of ITU-R Activities 1452-1525 MHz

33	Binckes	Method for Converting MSS Voice Traffic		
		Demand Forecasts into Spectrum		
		Requirements (MSS Networks above 1 GHz)		
34	Fisher	Minutes - July 19, 1994 Meeting		
35	Fisher	Minutes - August 16, 1994 Meeting		
36	Levin	New Mobile-Satellite Service Allocation in the		
		1559-1569 MHz Band (space to Earth)		
37	Jansky	Contribution to Regulatory Issues Section (VI) of		
	•	IWG-3 Preliminary Report		
38	NTIA	Spectrum Use Summary, 137 MHz - 5 GHz		
39	Binckes	Draft IWG-3 Report Element: section IV.A,		
		Advancement of Date of Entry Into Force-FN 746B		
40	LTaylor	Outline for U.S. Proposals Section of IWG-3		
		Preliminary Report		
41	Gould	Footnotes RR 731E and 733E to the 1610-1626.5		
		MHz Band		
42 ·	Lewellen	Draft Text for Section IX of IWG-3 Preliminary		
		Report, Recommendations for WRC-97 Agenda		
43	Fisher	Minutes - November 8, 1994 Meeting		
44	IWG-3	Preliminary Draft Report		
45	Rinaldo	Minutes - December 13, 1994 Meeting		

### APPENDIX 3.8.3

### Analysis of MSS Bands

### I. 1492-1525 MHz (Space to Earth)

Generic MSS in Region 2 only, except in the United States where the band is used for aeronautical telemetry. MSS subject to Resolution 46; PFD RR 2566.

- II. 1525-1544, 1545-1559 MHz (Space to Earth) and 1626.5-1645.5, 1646.5-1660.5 MHz (Earth to Space)
- A. <u>1525-1530 MHz</u> Generic MSS in Region 2 and 3; Primary maritime mobile satellite in Region 1; secondary land-mobile satellite service in Region 1 MSS subject to Resolution 46; PFD RR 2566, limited to non-speech low bit rate data transmissions.
- B. 1530-1544 (Space to Earth)/1626,5-1645.5 (Earth to Space) Generic MSS in seven countries; subject to priority for maritime distress and safety communications
- (1) 1530-1533/1631-1634.5 MHz Land MSS and maritime MSS, primary in all three regions.
- (2) <u>1626.5-1631.5 MHz</u> MSS primary in Regions 2 and 3; primary maritime MSS and secondary land MSS in Region 1.
- (3) 1533-1544/1635.5-1645.5 MHz Maritime MSS primary in all three regions; land MSS secondary.
  - (4) <u>1544-1545/1645.5-1646.5 MHz</u> MSS primary in all three regions.
- C. <u>1545-1559/1646.5-1660.5 MHz</u> MSS subject to Resolution 46; PFD RR 2566.
- (1) 1545-1555 (Space to Earth)/1646.5-1656.5 MHz (Earth to Space) Aeronautical safety MSS primary in all three regions.
- (2) 1555-1559 (Space to Earth)/1656.5-1660.5 (Earth to Space) MHz Land MSS primary in all three regions; in five countries, band is allocated to generic MSS and in Argentina and U.S. subject to priority for aeronautical safety services.
- D. <u>1660-1660.5 MHz (Earth to Space)</u> Land mobile satellite in all three regions. FN 730C provides alternative MSS allocation subject to coordination.
- III. 1610-1626.5 MHz (Earth to Space)/2483.5-2500 MHz (Space to Earth) Generic in all three regions, subject to Resolution 46.
  - A. 1610.6-1613.8 MHz Radio Astronomy issue 733E

feeder links ES's. This is an important consideration in a system where the exact locations and numbers of the feeder link ES's are unknown at the design stage.

Additionally, systems using these frequencies can use well developed technology in a band where propagation impairments do not result in significant cost impact. The resulting need for relatively small link margins can be exploited through the use of relatively low cost feeder link ES's.

### 8-17.7 GHz (Ku-Band):

One of the advantages of this range of frequencies is that it contains a virtually unused 500 MHz portion of spectrum that is currently included in the WARC-88 Allotment Plan allocations. There are also a number of other FSS bands available at Ku-Band, although coordination with VSAT's, TVRO's, and BSS feeder links may make implementation of MSS feeder links difficult. The desire to avoid the rain fading and site-diversity problems that are inherent at Ka-band also make this band attractive.

### 20-30 GHz (Ka-Band):

Among the reasons for choosing this part of the spectrum are that at present it is relatively lightly used, relatively easy to coordinate, and contains a significant bandwidth allocation. In addition, the utilization of narrower feeder link beams on the satellite, without recourse to large satellite reflectors, provides the additional link gain required to overcome rain fade effects. Finally, in system designs which provide for flexibility in the location of feeder link earth stations, due to either increased orbit altitude or the use of inter-satellite links, it is possible to locate feeder link stations in areas of low rainfall, thereby avoiding some of the rain attenuation problems normally associated with this frequency band.

### 3.2 Co-Directional vs. Reverse Direction Use of FSS Bands

### Co-Directional Use

In principle, any frequency band allocated to the FSS may be used codirectionally by MSS feeder links without modifications to the Table of Frequency Allocations. In practice, however, it is clear that not all FSS bands are attractive for

### Appendix 3.8.4

The coordination process for assignments of non-GSO MSS systems and fixed services (description of approach)

In the following, Administration A is the one planning to implement an assignment in a non-GSO MSS system. Administration B is the one whose FS assignments overlap with those of Administration A and could be affected. The proposed coordination approach would consist in applying the following steps (see Figure 1):

- a) An administration wishing to establish a non-GSO MSS system submits to the Bureau complete Appendix 3 information, including system specific characteristics, under § 2.6 of Section II of the Annex to Resolution 46 (WARC-92). This information shall include <u>all</u> the parameters required both to make the calculations required to assess compliance with Recommendation xxx [doc 2-2/Temp/83 Rev2] and to run a simulation on the standard computation program described in Annex 1 to Recommendation zzz [Doc 2-2/TEMP/80 Rev2] to check if the coordination thresholds specified in Recommendation xxx for the protection of the analogue and digital FS systems are met.
- b) The Bureau shall review the information for completeness and, performing the required calculations, shall assess the system's compliance with the limits set forth in Recommendation xxx [doc 2-2/TEMP/83 Rev2]. If the system's resultant parameters do not exceed the limits set forth in Recommendation xxx, there is no need for coordination with fixed services.
- c) If the system's parameters exceed the limits set forth in Recommendation xxx, the Bureau shall use the standard computation program described in Annex 1 of recommendation zzz and, taking into account the system-specific characteristics for the non-GSO MSS system and the reference characteristics of the FS systems in the band (s) involved, per § 2.5, Section II, Annex to Resolution 46 (WARC-92), calculate interference levels as appropriate to identify geographic areas and thus administrations in whose territory the protection criteria referred to in recommendation zzz for the reference analogue/digital FS systems are not met.
- d) Then the BR publishes both the Appendix 3 parameters and the list of administrations which it considers to be potentially affected. This list supersedes that mentioned in note 1 under 2.7.2 of the Annnex to Resolution 46.

Using the present provisions of Resolution 46, affected administrations are limited to those having FS assignments either "recorded in the Master Register" (2.5.4) or "not notified, but in use or planned to be brought into use within the next three years" (2.5.5), and which in addition might be affected according to the results of the pfd/FDP calculations and/or the application of the method in Recommendation zzz. Since the BR can know only of assignments in the first category (recorded in the Master Register), this list cannot contain administrations in the second category (with assignments not notified, but in use or planned to be brought into use within the next three years). The administrations falling in this second category, or for which an omission may

have occurred should therefore have the possibility to make themselves known, which is the purpose of step e).

- e) Administrations review the published information (per § 2.8, Section II, Annex to Resolution 46 (WARC-92)) with a view to comment within six months from the date of publication of the relevant Special Section, and provide technical details of the terrestrial stations upon which any negative comment is based.
  - If, within the six month period referred to above, no objection is received from any administration, including those identified by the Bureau in the Special Section, the notifying administration is considered as having successfully coordinated the non-GSO MSS system with the fixed services.
  - Upon receipt of the publication mentioned in section 2.7.2, an administration which has not been included in the list of affected administrations by the BR may, within the six month period referred to above, request to be included if it considers that it could be affected (Paragraph 2.8 of Annex to Resolution 46). However, this inclusion needs to be validated by the BR on the basis of the criteria mentioned in paragraph d) above.
- f) The notifying administration and any administration that provided an objection on the planned non-GSO MSS system within the six month period mentioned in paragraph e) would enter into detailed coordination consultations using actual FS stations and characteristics (see Annex A).
- g) Administrations should then communicate to the Bureau any modifications to the published characteristics of their respective networks or stations required to reach agreement on the coordination. The Bureau would publish these modifications indicating that they resulted from the efforts of the administrations concerned to reach agreement on the coordination of the non-GSO MSS system.

This procedure retains the current approach of REsolution 46 procedure, and is expected to necessitate only straight forward modification to the existing text of Resolution 46 procedure. A possible text for these modifications is provided as an illustration of this simplified approach (see Annex B).

# FCC INDUSTRY ADVISORY COMMITTEE

### FOR THE

# ITU 1995 WORLD RADIO COMMUNIÇATION CONFERENCE

INTERIM REPORT

OF

**INFORMAL WORKING GROUP 4** 

Jack Wengryniuk Chair

Michael L. Richmond Vice Chair

### Interim Report of WRC-95 Industry Advisory Committee Informal Working Group 4 (Feeder Links)

•			. •	
1.	Int	~~111	ctio	n
I.	ши		LUU	11

- 2. Overall Spectrum Requirements for MSS Feeder Links
  - 2.1 The need for sufficient spectrum
  - 2.2 First generation vs. second generation requirements
- 3. Considerations Relating to Choice of Frequency Bands for MSS Feeder Links
  - 3.1 Possible impact on MSS system design, operation, and cost
  - 3.2 Co-directional vs. reverse direction use of a given band
- 4. Feasibility of Frequency Sharing Between NGSO MSS Feeder Links and Other Services and Between Multiple NGSO MSS Feeder Link Systems
  - 4.1 Co-directional frequency sharing between NGSO MSS Feeder Links and GSO FSS systems
  - 4.2 Reverse direction frequency sharing between NGSO MSS Feeder Links and GSO FSS systems
  - 4.3 Frequency sharing between NGSO MSS Feeder Links and Fixed Service Networks
    - 4.3.1 Interference from NGSO MSS Satellite Feeder Link into Fixed Service Station
    - 4.3.2 Interference from Fixed Service Station into NGSO MSS Satellite Feeder Link
    - 4.3.3 Interference Between NGSO MSS Feeder Link Earth Station and Fixed Service Station
    - 4.3.4 Reverse Band Working of NGSO MSS Feeder Links and the FS
  - 4.4 Frequency sharing between NGSO MSS Feeder Links and the Aeronautical Radionavigation Service (ARNS) in the 5000-5250 MHz Band
    - 4.4.1 Sharing between Non-GSO/MSS feeder links and MLS
    - 4.4.2 Sharing between NGSO MSS feeder links and other services
  - 4.5 Frequency Sharing Between Multiple NGSO MSS Feeder Link Networks
    - 4.5.1 Summary of Results of Recent Analyses and Computer Simulations
    - 4.5.2 Summary of Mitigation Techniques
- 5. Regulatory and Procedural Provisions for NGSO MSS Feeder Link Networks
  - 5.1 Introduction
  - 5.2 **Possible Regulatory/Procedural Revisions** 
    - 5.2.1 General
    - 5.2.2 Changes to Article 8
      5.2.2.1 Bands Below 17.7 GHz
      5.2.2.2 Bands Above 17.7 GHz
    - 5.2.3 Changes to Article 11 and/or Resolution 46
    - 5.2.4 Changes to Article 29
- 6. U.S. Proposals for MSS Feeder Link Spectrum

### 1. Introduction

Informal Working Group 4 (IWG-4) of the FCC Industry Advisory Committee for WRC-95 is tasked with developing U.S. industry consensus positions on proposals for preferred FSS frequency bands which could support MSS feeder link spectrum. As such, the IWG has been considering a number of issues related to the provision of MSS feeder link spectrum. This interim report represents the current views of IWG-4 on this topic and work shall continue through the early part of 1995 in order to resolve all outstanding issues.

IWG-4 has met six times to date, and was well attended on all occassions by U.S. industry and government participants (See Attachment 1 for IWG-4 Participants List). It should be noted that many of the participants in IWG-4 were also very actively involved in a similar international effort on this same topic coordinated by the International Telecommunications Union (i.e. ITU-R Task Group 4/5). Task Group 4/5 was responsible for developing the technical basis for MSS feeder link use of various FSS bands and this Task Group has recently completed its work and will be submitting a report to the Conference Preparatory Meeting.

While there were times where this cross participation in IWG-4 and Task Group 4/5 resulted in scheduling conflicts, in general IWG-4 has benefited greatly from this fact. Much of the work done in preparation for, and during, the international meetings of Task Group 4/5 was directly applicable to the work of IWG-4. In fact, much of the content of this Interim Report has already been vetted internationally and this will no doubt serve to further its acceptance at WRC-95.

This Interim Report contains reasonably stable text pertaining to the Overall Spectrum Requirements for MSS Feeder Links (Section 2), the Considerations Relating to the Choice of Frequency Bands (Section 3) and Feasibility of Frequency Sharing Between MSS Feeder Links and Other Services (section 4). In the area of Regulatory and Procedurtal Issues (Section 5), much of the text recently agreed by ITU-R Task Group 4/5 has been included in this Interim Report. While IWG-4 participants were actively involved in the development of this text, and endorse it, there may be some areas still requiring the specific attention of the IWG. Finally, specific U.S. Proposals for MSS Feeder Link Bands have yet to be developed, however, as can be seen in Section 6 of this Interim Report, IWG-4 has been able to narrow the scope of this topic and shall be considering a specific set of frequency bands in its further work.